

CT-5372/CT-5372E

Multi-DSL Router



COMTREND
Leading the Communication Trend



Description

The CT-5372/CT-5372E is a leading Multi-DSL router that can support both ADSL2+ and VDSL2. The CT-5372 is for ADSL2+/VDSL2 over POTS (Annex A) while the CT-5372E is for ADSL2+/VDSL2 over ISDN (Annex B).

VDSL2 is a brand new standard and technology that is perfectly suitable for triple play (Video, Voice and Data) applications. Four 10/100 Base-T Ethernet ports and optional USB host/device are integrated to provide wired LAN connectivity with an integrated 802.11g WiFi WLAN Access Point (AP) for wireless connectivity.

The CT-5372/CT-5372E is a cost effective solution, designed to meet the needs of ISPs and carriers that intend to use one DSL device to cover end users in different loop range areas. Using only one DSL device creates savings for the TCO of ISP and carrier, whilst simultaneously providing valuable services without the need for upgrade.

Features

- Supports both ADSL2+ and VDSL2
- Automatically switches to ADSL2+ or VDSL2 according to the port setting of DSLAM
- Wi-Fi Certified
- UPnP
- Integrated 802.11g AP
- WPA and 802.1x
- RADIUS client
- IP/MAC address filtering
- Static route/RIP/RIP v2 routing functions
- Dynamic IP assignment
- IP QoS
- NAT/PAT
- IGMP Proxy and fast leave
- DHCP Server/Relay/Client
- DNS Proxy
- Auto PVC configuration
- Per-VC packet level QoS
- Up to 16 VCs
- Embedded SNMP agent
- Web-based management
- Remote configuration and upgrade
- Supports TR-069/TR-098/TR-111 for Remote Management
- Configuration backup and restoration
- FTP server
- TFTP server

Applications Diagram



CT-5372/CT-5372E

Multi-DSL Router

Specifications

Rear Panel

RJ-11 X1 for ADSL2+/VDSL2, RJ-45 X 4 for LAN, Reset Button X 1, Power switch X 1, optional USB host/device

DSL

ADSL standard	ITU-T G.992.5, ITU-T G.992.3, ITU-T G.992.1, ANSI T1.413 Issue 2, AnnexM
ADSL2+	Downstream : 24 Mbps Upstream : 1.3 Mbps
VDSL2 standard	ITU-T G.993.2 (supporting profile 8a, 8b, 8c, 8d, 12a, 12b, 17a)
VDSL2	Downstream : 100 Mbps Upstream : 60 Mbps

Ethernet

Standard	IEEE 802.3, IEEE 802.3u
10/100 BaseT	Auto-sense
MDI/MDX support	Yes

Wireless

Standard	IEEE802.11g, backward compatible with 802.11b
Encryption	64, 128-bit Wired Equivalent Privacy (WEP) Data Encryption
Channels	11 Channels (US, Canada)/ 13 Channels (Europe)/ 14 Channels (Japan)
Data Rate	Up to 54Mbps
WPA	Yes
IEEE 802.1x	Yes

ATM Attributes

RFC 2364 (PPPoA), RFC 2684 (RFC 1483) Bridge/Route; RFC 2516 (PPPoE); RFC 1577 (IPoA)	
Support PVCs	16
AAL type	AAL5
ATM service class	UBR/CBR/VBR
ATM UNI support	UNI 3.1/4.0
OAM F4/F5	Yes

Management

SNMP, Telnet, Web-based management, Configuration backup and restoration
Software upgrade via HTTP, TFTP server, or FTP server
Supports TR-069/TR-098/TR-111 for Remote Management

Bridge Functions

Transparent bridging and learning	IEEE 802.1d
VLAN support	Yes
Spanning Tree Algorithm	Yes
IGMP Proxy	Yes

Routing Functions

Static route, RIP, and RIPv2, NAT/PAT, DHCP Server/DHCP Relay, DNS Proxy, ARP

Security Functions

Authentication protocols PAP, CHAP,
TCP/IP/Port filtering rules, Port triggering/Forwarding, Packet and MAC address filtering, access control, SSH

Application Passthrough

PPTP, L2TP, IPSec, VoIP, Yahoo messenger, ICQ, RealPlayer, NetMeeting, MSN, X-box, etc

OS Supported for USB driver

Windows 2000/XP/ME/98SE

Power Supply

External power adapter 100-240Vac, 15VDC /1.6A

Environment Condition

Operating temperature	0 ~ 50 degrees Celsius
Relative humidity	5 ~ 95% (non-condensing)

Dimensions

205 mm (W) x 48 mm (H) x 145 mm (D)

Kit Weight (1*CT-5372 or CT-5372E, 1* RJ-11 cable, 1* RJ-45 cable, 1* USB cable, 1* Power Adapter, 1* CD-ROM)

1000 grams

Certifications

FCC Part 15 class B, FCC Part 68, CE

Note: Specifications are subject to change without notice.

Taiwan:
3F-1, No.10, Lane 609, Chung Hsin Road
Section 5, San Chung, Taipei, Taiwan 24159
Tel: 886-2-2999-8261
Fax: 886-2-2999-8497

China:
Room 102, No.8, LiJing Garden, Yushan Town,
Kunshan City, Jiangsu Province, China
Tel: 86-512-57383156, 86-512-57383157,
86-512-57384515
Fax: 86-512-57383155

Spain:
Edif. América II C/Proción,7 portal 3 bajo H 28023 Madrid,
Spain
Tel: 34-917990403
Fax: 34-913510999

France:
87, Rue du Gouverneur Général Félix Eboué 92130
Issy-les-Moulineaux, France
Tel: 33-1-70715700
Fax: 33-1-70715701

Czech Republic:
TOKOVO, Jankovcova 1518/2, 170 00 Prague 7, Czech Republic
Tel: 420-266-782040
Fax: 420-266-782990

USA:
15375 Barranca Parkway, Suite C-104 Irvine,
CA 92618, USA
Tel: 1-949-7539640
Fax: 1-949-7539020

Canada:
300-1275 West 6th Ave. Vancouver, BC V6H
1A6, Canada
Tel: 1-949-7539640
Fax: 1-949-7539020

Brazil:
Rua Vergueiro, 2087 cj. 101, 04101-000 Sao
Paulo, SP - Brazil
Tel: 55-11-50878831 DS_CT5372/CT5372E_R1.0_070407



COMTREND CORPORATION

Global contact: sales@comtrend.com
Website: www.comtrend.com

